



3/2-way or 2 × 3/2-way solenoid valve for pneumatic applications

- Compact design
- Second connection for shut-off function
- Low power consumption
- Fast switching times



Product variants described in the data sheet may differ from the product presentation and description.

Can be combined with

	Type 8640 Modular valve island for pneumatics	▶
	Type 8644 AirLINE SP electropneumatic automation system	▶
	Type MKRS Redundancy valve block for safety-related shut-off function	▶
	Type 8647 AirLINE SP – electropneumatic automation system	▶
	Type 2505 10 mm socket for Bürkert small solenoid valves	▶

Type description

Type 6524 consists of a pilot flipper solenoid valve Type 6144 and a pneumatic seat valve. The flipper action system allows the switching of high pressures combined with low power consumption and short switching times. All the valves are equipped with manual override as standard. The 2 × 3/2-way valve variant is a combination of two pilot flipper solenoid valves Type 6144 and one pneumatic seat valve. The valve is also available with a second connection (press-fit cable), which makes a safe shut-off function possible.

Table of contents

1. General technical data	3
2. Circuit functions	4
3. Approvals and conformities	4
3.1. General notes	4
3.2. Conformity	4
3.3. Standards	4
3.4. Explosion protection.....	5
3.5. North America (USA/Canada)	5
4. Materials	5
4.1. Bürkert resistApp	5
5. Dimensions	6
5.1. Standard variant 3/2-way	6
5.2. Standard variant 2 × 3/2-way	6
5.3. Second connection for shut-off function 3/2-way	7
5.4. Second connection for shut-off function 2 × 3/2-way	7
6. Product design and assembly	8
6.1. Product assembly	8
Standard variant 3/2-way	8
Standard variant 2 × 3/2-way	8
6.2. Distinguishing features valve revisions.....	9
7. Ordering information	9
7.1. Bürkert eShop	9
7.2. Bürkert product filter	9
7.3. Ordering chart standard variant.....	10
7.4. Ordering chart second connection shut-off function	11
7.5. Ordering chart accessories.....	11

1. General technical data

Product properties	3/2-way valve	2 × 3/2-way valve
Dimensions	Further information can be found in chapter "5. Dimensions" on page 6.	
Material		
Seal	FKM, NBR, PUR	
Body	PPS, polyamide	
Weight	20 g	40 g
Manual override	Standard	
Orifice	DN 4.0	
Pneumatic module	With plug-in coupling, Ø 6 mm, Ø ¼"	
Circuit function	C and D Further information can be found in chapter "2. Circuit functions" on page 4.	
Performance data		
Duty cycle	100 % continuous operation	
Switching frequency	Approx. 1000 c.p.m.	
Switching time ¹⁾	Opening: < 10 ms Closing: < 10 ms	
Electrical data		
Operating voltage	24 V DC ²⁾	
Nominal power	0.8 W	2 × 0.8 W
Voltage tolerance	± 10 %	
Medium data		
Operating medium	Lubricated or oil-free compressed dry air, neutral gases (5 µm filter recommended)	
Medium temperature	- 10 °C...+ 50 °C	
Product connections		
Electrical connection	Rectangular plug with 2 pins, raster 5.08 mm	Rectangular plug with 3, pins raster 2.54 mm
Approvals and conformities		
Degree of protection	IP40 with rectangular cable plug	
Protection class	III according to VDE 0580	
Explosion protection	Further information can be found in chapter "3.4. Explosion protection" on page 5.	
North America (USA/Canada)	Further information can be found in chapter "3.5. North America (USA/Canada)" on page 5.	
Environment and installation		
Installation position	As required, preferably with actuator upright	
Mounting	With 2 screws M2 × 20	With 2 screws M2 × 28
Ambient temperature	- 10 °C...+ 55 °C	

1.) Measurement according to ISO 12238

2.) 10 % residual ripple permissible

2. Circuit functions

Symbol	Description
	Circuit function C (CF C) 3/2-way solenoid valve Servo-controlled, with manual override Normally closed
	Circuit function C (CF C) 2 x 3/2-way solenoid valve Servo-controlled, with manual override Normally closed
	Circuit function C (CF C) 3/2-way solenoid valve Servo-controlled Normally closed
	Circuit function C (CF C) 2 x 3/2-way solenoid valve Servo-controlled Normally closed
	Circuit function D (CF D) 3/2-way solenoid valve Servo-controlled, with manual override Normally open
	Circuit function D (CF D) 3/2-way solenoid valve Servo-controlled Normally open

3. Approvals and conformities

3.1. General notes

- The approvals and conformities listed below must be stated when making enquiries. This is the only way to ensure that the product complies with all required specifications.
- Not all available variants can be supplied with the below mentioned approvals or conformities.



3.2. Conformity

In accordance with the Declaration of Conformity, the product is compliant with the EU Directives.


3.3. Standards

The applied standards which are used to demonstrate compliance with the EU Directives are listed in the EU-Type Examination Certificate and/or the EU Declaration of Conformity.

3.4. Explosion protection

Approval	Description
 	<p>Optional: Explosion protection EU type examination certificate: PTB 07 ATEX 2048 X / IECEx PTB 07.0063 X</p> <p>As a category 2 device suitable for zone 1 and zone 2 (optional).</p> <p>ATEX: PTB 07 ATEX 2048 X II 2G Ex ia IIC T6...T4 Gb</p> <p>IECEX: IECEx PTB 07.0063 X Ex ia IIC T6...T4 Gb</p>


3.5. North America (USA/Canada)

Approval	Description
	<p>Optional (valid for pilot control valve): UL Recognized for the USA and Canada ¹⁾ The pilot control valves are UL Recognized for the USA and Canada according to:</p> <ul style="list-style-type: none"> • UL 429 (electrically operated valves) • CAN/CSA-C22.2 No. 139

1.) This device is intended to be used with a NEC Class 2 power source or NEC Class 2 transformer in accordance with UL1310 or UL1585.

4. Materials

4.1. Bürkert resistApp



Bürkert resistApp – Chemical resistance chart

You want to ensure the reliability and durability of the materials in your individual application case? Verify your combination of media and materials on our website or in our resistApp.

[Start chemical resistance check](#)

DTS 1000021454 EN Version: S Status: RL (released | freigegeben | valide) printed: 19.02.2026

6. Product design and assembly

6.1. Product assembly

Standard variant 3/2-way

Sectional drawing Pilot control Type 6144	Connection overview	Circuit function
<p>Pilot control exhaust air</p> <p>3 (R)</p> <p>2 (A)</p> <p>1 (P)</p>	<p>Pilot control exhaust air</p> <p>3/R</p> <p>2/A</p> <p>1/P</p>	<p>CF C</p> <p>CF D</p>

Standard variant 2 × 3/2-way

Sectional drawing	Connection overview	Circuit function
<p>(12)</p> <p>(14)</p> <p>Pilot control exhaust air</p> <p>5 (S)</p> <p>4 (A)</p> <p>1 (P)</p> <p>2 (B)</p> <p>3 (R)</p>	<p>12 Hand lever</p> <p>14 Assignment</p> <p>Pilot control exhaust air</p> <p>5 (S)</p> <p>4 (A) Bit „n“</p> <p>1 (P)</p> <p>2 (B) Bit „n+1“</p> <p>3 (R)</p>	<p>CF C</p> <p>2 × 3/2-way solenoid valve</p>

DTS 1000021454 EN Version: S Status: RL (released | freigegeben | valide) printed: 19.02.2026

6.2. Distinguishing features valve revisions

Note:


- The pneumatic flange pattern has been standardised for Type 6524, 3/2-way.
- There is a difference in the flange pattern variants (REV. 1/REV. 2). The external dimensions remain identical.
- Before the pneumatic installation, the compatibility with the present valve island must be checked (see operating instructions of the corresponding valve island).

The valve revisions can be distinguished by the following features:

Valves Type 6524	Valve REV. 1	Valve REV. 2
Article no.	Distinguishing by Article no. see "7. Ordering information" on page 9	
Visual distinction	<p>REV. 1 Single valves Type 6524 and Type 6525 with flange interface „FM14“</p> <p>Different size of the channels</p> <p>REV. 2 Single valves Type 6524 and Type 6525 with flange interface „FM20“</p>	
Information label	There is a corresponding information label on the relevant valve which indicates that the valve has been overhauled. This information label must be removed before assembly.	
Compatibility with the pneumatic modules of the island by means of the working ports	<p>black parallel</p>	<p>blue wavy</p>

7. Ordering information

7.1. Bürkert eShop




Bürkert eShop – Easy ordering and quick delivery

You want to find your desired Bürkert product or spare part quickly and order directly? Our online shop is available for you 24/7. Sign up and enjoy all the benefits.

[Order online now](#)

7.2. Bürkert product filter



Bürkert product filter – Get quickly to the right product

You want to select products comfortably based on your technical requirements? Use the Bürkert product filter and find suitable articles for your application quickly and easily.

[Try out our product filter](#)

7.3. Ordering chart standard variant

Hinweis:

- The pneumatic flange pattern has been standardised for Type 6524, 3/2-way.
- There is a difference in the flange pattern variants (REV. 1/REV. 2). The external dimensions remain identical.
- Before the pneumatic installation, the compatibility with the present valve island must be checked (see operating instructions of the corresponding valve island).

Circuit function	Orifice	Q _{Nm} value air	Voltage/ Frequency	Pressure range	Integrated power savings electronics	Article no.	
	[mm]	[l/min] ¹⁾	[V/Hz]	[bar] ²⁾		Valves REV. 1	Valves REV. 2
3/2-way							
CF C 3/2-way solenoid valve Servo-controlled, with manual override Normally closed 	4	300	24 V DC ³⁾	Vac...10 ⁴⁾	–	20029915 ☒ (186258 ☒) ⁶⁾	20029923 ☒ (20013119 ☒) ⁶⁾
			24 V DC ³⁾	1...10	–	20029913 ☒ (186257 ☒) ⁶⁾	20029921 ☒ (20013114 ☒) ⁶⁾
			24 V DC ³⁾	2.5...10	–	20029910 ☒ (184043 ☒) ⁶⁾	20029918 ☒ (365606 ☒) ⁶⁾
CF D 3/2-way solenoid valve Servo-controlled, with manual override Normally open 	4	300	24 V DC ³⁾	2.5...10	–	20029911 ☒ (184400 ☒) ⁶⁾	20029919 ☒ (365609 ☒) ⁶⁾
2 × 3/2-way							
CF C 2 × 3/2-way solenoid valve Servo-controlled, with manual override Normally closed 	4	300	24 V DC ³⁾	1...10 ⁴⁾	Yes ⁵⁾	186259 ☒	
			24 V DC ³⁾	2.5...10	Yes ⁵⁾	186260 ☒	
			24 V DC ³⁾	2.5...10	No	204710 ☒	

1.) Measurement at + 20 °C, 6 bar at the valve inlet and 1 bar differential pressure
 2.) Pressure data: overpressure to atmospheric pressure
 3.) 10 % residual ripple permissible
 4.) Variant with auxiliary pilot air
 5.) Applicable on valve island Type 8640, AirLINE system Type 8644 or valve blocks
 6.) The Article no. can no longer be ordered. Order the superior set instead.

DTS 1000021454 EN Version: S Status: RL (released | freigegeben | valide) printed: 19.02.2026

7.4. Ordering chart second connection shut-off function

Circuit function	Orifice	Q _{Nm} value air	Voltage/ Frequency	Pressure range	Integrated power savings electronics	Article no.	
	[mm]	[l/min] ^{1.)}	[V/Hz]	[bar] ^{2.)}		Valves REV.1	Valves REV.2
3/2-way, without manual override							
CF C 3/2-way solenoid valve Servo-controlled Normally closed 	4	300	24 V DC ^{3.)}	Vac...10 ^{4.)}	–	o. r.	o. r.
			24 V DC ^{3.)}	1...10	–	o. r.	o. r.
			24 V DC ^{3.)}	2.5...10	–	20029916 ☒ (285545 ☒) ^{6.)}	20029924 ☒ (20013136 ☒) ^{6.)}
CF D 3/2-way solenoid valve Servo-controlled Normally open 	4	300	24 V DC ^{3.)}	2.5...10	–	o. r.	o. r.
2 × 3/2-way, without manual override							
CF C 2 × 3/2-way solenoid valve Servo-controlled Normally closed 	4	300	24 V DC ^{3.)}	1...10 ^{4.)}	Yes ^{5.)}	o. r.	
			24 V DC ^{3.)}	2.5...10	Yes ^{5.)}	285547 ☒	
			24 V DC ^{3.)}	2.5...10	No	300818 ☒	

o. r. = on request

- 1.) Measurement at + 20 °C, 6 bar at the valve inlet and 1 bar differential pressure
- 2.) Pressure data: overpressure to atmospheric pressure
- 3.) 10 % residual ripple permissible
- 4.) Variant with auxiliary pilot air
- 5.) Applicable on valve island Type 8640, AirLINE system Type 8644 or valve blocks
- 6.) The Article no. can no longer be ordered. Order the superior set instead.

7.5. Ordering chart accessories

Description	Article no.
Cable plug 10 mm with cable, 2-pin, rectangular plug, straight, cable length: 3 m (Type 2505)	133486 ☒
Cable plug 10 mm with cable, 2-pin, rectangular plug, straight, cable length: 0.3 m (Type 2505)	644068 ☒
Cable plug 10 mm, 2-pin, rectangular plug, straight (Type 2505)	644067 ☒
Cover plate for solenoid valves Type 6524/6525 (REV. 1) for 5/2-way valve position	650373 ☒
Cover plate for solenoid valves Type 6524/6525 (REV. 2) for 2 × 3/2-way valve position	661092 ☒
Spare valve seals FM20 for Type 6524, 2 × 3/2-way solenoid valve, REV. 1/REV. 2, 12 seals	20016305 ☒
Spare valve seals FM15 for Type 6524, 3/2-way solenoid valve, REV. 1, 12 seals	20024333 ☒
Spare valve seals FM24 for Type 6524, 3/2-way solenoid valve, REV. 2, 12 seals	20024336 ☒

DTS 1000021454 EN Version: S Status: RL (released | freigegeben | valide) printed: 19.02.2026